



C A T A L O G U E



SHANDONG VCHER ELECTRICAL APPLIANCE CO., LTD.

FACTORY, SALES & MARKETING OFFICE (LAIZHOU)
WEST SHILI PU, HUTOUYA INDUSTRY ZONE LAIZHOU CITY,
SHANDONG PROVINCE,
CHINA 261428
TEL: +86 535 288 2217
FAX: +86 535 288 2267
E_MAIL: INFO@VCHER.COM.CN

SALES & MARKETING OFFICE (QINGDAO)
ROOM 6-609, #40, XIANGGANG MID ROAD, SHINAN DISTRICT, QINGDAO CITY
SHANDONG PROVINCE
CHINA 266100
TEL: +86 18653266936
E_MAIL: GUANENH@VCHER.COM.CN
[HTTPS://WWW.VCHER.COM.CN](https://www.vcher.com.cn)



V2020.08

PROFESSIONAL KITCHEN REFRIGERATION EQUIPMENT

>> COMPANY PROFILE



SHANDONG VCHER ELECTRICAL APPLIANCE CO., LTD. is a professional manufacturer of commercial kitchen refrigeration equipment, which is engaged in research and development, production, sales and after-sales service. Our factory located in Laizhou city Shandong province China. It takes only one and half hours from Qingdao airport to our company and two hours from Qingdao port.

Our factory covers total 80,000 square meters, we produce 150,000 sets of commercial refrigerators and freezers every year. Our products are with CE, RoHS, SAA, ITACS, ETL Sanitation, cETL certifications ,CCC, ISO9000 and so on. The products have already exported to more than 36 countries. It is the first choice for hotels, restaurants, chain catering kitchens, enterprises and public institutions, and school etc. Shandong Vcher Electrical Appliance Co., Ltd provides customers with a beautiful, safe and excellent kitchen. Meanwhile, we make great efforts to protect our living environment.



>> CABINET RANGE
VENTILATED REFRIGERATED GN CABINET 650 SERIES - SINGLE DOOR



GN650TN



GN650TNM



GN650TNG



GN650BT



GN650BTM



GN650BTG

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
GN650TN	-2 ~ +8	624×700×1401	740×830×2010	685	113	123	230V/50Hz	39
GN650BT	-18 ~ -22	624×700×1401	740×830×2010	685	131	141	230V/50Hz	39
GN650TNM	-2 ~ +8	624×700×1401	740×830×2010	685	125	135	230V/50Hz	39
GN650BTM	-18 ~ -22	624×700×1401	740×830×2010	685	134	144	230V/50Hz	39
GN650TNG	+2 ~ +8	624×700×1401	740×830×2010	685	129	139	230V/50Hz	39
GN650BTG	-18 ~ -20	624×700×1401	740×830×2010	685	161	171	230V/50Hz	39



>> CABINET RANGE
VENTILATED REFRIGERATED GN CABINET 650 SERIES - DOUBLE DOORS



GN1410TN



GN1410TNM



GN1410TNG



GN1410BT



GN1410BTM



GN1410BTG

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
GN1410TN	-2 ~ +8	1364×700×1401	1480×830×2010	1476	188	203	230V/50Hz	15
GN1410BT	-18 ~ -22	1364×700×1401	1480×830×2010	1476	202	217	230V/50Hz	15
GN1410TNM	-2 ~ +8	1364×700×1401	1480×830×2010	1476	206	221	230V/50Hz	15
GN1410BTM	-18 ~ -22	1364×700×1401	1480×830×2010	1476	221	236	230V/50Hz	15
GN1410TNG	+2 ~ +8	1364×700×1401	1480×830×2010	1476	219	234	230V/50Hz	15
GN1410BTG	-18 ~ -20	1364×700×1401	1480×830×2010	1476	261	276	230V/50Hz	15



>> COUNTER RANGE
VENTILATED REFRIGERATED GN COUNTER - WITH GLASS DOOR / BACK SPLASH



GN2100TNG



GN2200TN



GN3100TNG



GN3200TN



GN4100TNG



GN4200TN

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
GN2100TNG	+2 ~ +8	795×580×589	1360×700×860	314	98	113	230V/50Hz	48
GN3100TNG	+2 ~ +8	1230×580×589	1795×700×860	465	126	143	230V/50Hz	38
GN4100TNG	+2 ~ +8	1663×580×589	2230×700×860	616	150	170	230V/50Hz	32
GN2200TN	-2 ~ +8	795×580×589	1360×700×960	314	95	110	230V/50Hz	48
GN3200TN	-2 ~ +8	1230×580×589	1795×700×960	465	125	142	230V/50Hz	38
GN4200TN	-2 ~ +8	1663×580×589	2230×700×960	616	152	172	230V/50Hz	32



>> COUNTER RANGE
VENTILATED REFRIGERATED BAKERY COUNTER



PA2100TN



PA3100TN



PA2200TN



PA3200TN

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
PA2100TN	+2 ~ +8	945×680×589	1510×800×860	428	105	120	230V/50Hz	30
PA2200TN	+2 ~ +8	945×680×589	1510×800×960	428	116	131	230V/50Hz	30
PA3100TN	+2 ~ +8	1455×680×589	2020×800×860	635	132	150	230V/50Hz	28
PA3200TN	+2 ~ +8	1455×680×589	2020×800×960	635	146	164	230V/50Hz	28



>> COUNTER RANGE
VENTILATED REFRIGERATED SALAD COUNTER



SH2000/700



SH3000/700



SH2000/800



SH3000/800

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
SH2000/700	+2 ~ +8	795×580×589	1360×700×1085	396	100	120	230V/50Hz	48
SH2000/800	+2 ~ +8	945×680×589	1510×800×1085	459	115	135	230V/50Hz	30
SH3000/700	+2 ~ +8	1230×580×589	1795×700×1085	470	121	146	230V/50Hz	38
SH3000/800	+2 ~ +8	1455×680×589	2020×800×1085	576	145	173	230V/50Hz	28



>> COUNTER RANGE
VENTILATED REFRIGERATED MARBLE TOP PIZZA COUNTER



▾ PZ1610TN



▾ PZ2600TN



▾ PZ3600TN



▾ PZ2610TN



▾ GN3100TNPZ



▾ PA3100TNPZ



▾ GN2100TNPZ



▾ PA2100TNPZ



▾ GN4100TNPZ

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
PZ1610TN	+2 ~ +8	439×680×589	1515×800×1000	221	256	271	230V/50Hz	28
PZ2600TN	+2 ~ +8	949×680×589	1510×800×1000	428	234	249	230V/50Hz	28
PZ2610TN	+2 ~ +8	949×680×589	2025×800×1000	428	334	354	230V/50Hz	28
PZ3600TN	+2 ~ +8	1459×680×589	2025×800×1000	635	294	314	230V/50Hz	28
GN2100TNPZ	-2 ~ +8	795×580×589	1360×700×860	314	156	171	230V/50Hz	48
GN3100TNPZ	-2 ~ +8	1230×580×589	1795×700×860	465	205	222	230V/50Hz	38
GN4100TNPZ	-2 ~ +8	1663×580×589	2230×700×860	616	236	256	230V/50Hz	32
PA2100TNPZ	+2 ~ +8	945×680×589	1510×800×860	428	206	221	230V/50Hz	30
PA3100TNPZ	+2 ~ +8	1455×680×589	2020×800×860	635	240	260	230V/50Hz	28



>> SALADETTE RANGE
STATIC SALADETTE



↓ S900



↓ S901



↓ S902



↓ S903



↓ S903 TOP S/S

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
S900	+2 ~ +8	830×595×500	900×700×860	257	70	81	230V/50Hz	72
S901	+2 ~ +8	830×595×500	900×700×860	257	72	83	230V/50Hz	72
S902	+2 ~ +8	975×595×500	1045×700×860	302	80	91	230V/50Hz	60
S903	+2 ~ +8	1295×595×500	1365×700×860	400	107	122	230V/50Hz	48
S903 TOP S/S	+2 ~ +8	1295×595×500	1365×700×860	400	110	130	230V/50Hz	48





VRX WITH FLAT GLASS



VRX WITH CURVED GLASS



VRX WITH S/S LID

VRX330 SERIES

VRX850



VRX1000



VRX1200



VRX1400



VRX1500



VRX1600



VRX1800



VRX2000



VRX380 SERIES



Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (No. of GN Pans)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
VRX850/330	+2 ~ +8	445×245×155	850×335×440	GN1/4×3	32	34	230V/50Hz	539
VRX850/380	+2 ~ +8	445×305×155	850×395×440	GN1/3×1+GN1/2×1	35	37	230V/50Hz	469
VRX1000/330	+2 ~ +8	645×245×155	1000×335×440	GN1/4×4	35	38	230V/50Hz	462
VRX1000/380	+2 ~ +8	645×305×155	1000×395×440	GN1/3×2+GN1/2×1	38	41	230V/50Hz	385
VRX1200/330	+2 ~ +8	845×245×155	1200×335×440	GN1/4×5	39	43	230V/50Hz	392
VRX1200/380	+2 ~ +8	845×305×155	1200×395×440	GN1/3×3+GN1/2×1	42	46	230V/50Hz	322
VRX1400/330	+2 ~ +8	1045×245×155	1400×335×440	GN1/4×6	43	48	230V/50Hz	343
VRX1400/380	+2 ~ +8	1045×305×155	1400×395×440	GN1/3×4+GN1/2×1	45	50	230V/50Hz	287
VRX1500/330	+2 ~ +8	1145×245×155	1500×335×440	GN1/4×7	43	48	230V/50Hz	308
VRX1500/380	+2 ~ +8	1145×305×155	1500×395×440	GN1/3×5+GN1/2×1	49	54	230V/50Hz	259
VRX1600/330	+2 ~ +8	1245×245×155	1600×335×440	GN1/4×7	45	50	230V/50Hz	301
VRX1600/380	+2 ~ +8	1245×305×155	1600×395×440	GN1/3×7	51	56	230V/50Hz	252
VRX1800/330	+2 ~ +8	1445×245×155	1800×335×440	GN1/4×8	52	57	230V/50Hz	266
VRX1800/380	+2 ~ +8	1445×305×155	1800×395×440	GN1/3×8	55	60	230V/50Hz	224
VRX2000/330	+2 ~ +8	1645×245×155	2000×335×440	GN1/4×10	57	62	230V/50Hz	238
VRX2000/380	+2 ~ +8	1645×305×155	2000×395×440	GN1/3×9	62	68	230V/50Hz	203

>> STORAGE RANGE
UPRIGHT CHILLER & FREEZER



DR200
DF200



DR200 S/S
DF200 S/S



DR200 G



DR400
DF400



DR400 S/S
DF400 S/S



DR400 G



DR600
DF600



DR600 S/S
DF600 S/S



DR600 G

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
DR200	0 ~ +10	510×485×620	600×615×870	140	46	51	230V/50Hz	114
DF200	-10 ~ -22	510×485×620	600×615×870	140	46	51	230V/50Hz	114
DR400	0 ~ +10	510×485×1620	600×615×1870	360	73	78	230V/50Hz	57
DF400	-10 ~ -22	510×485×1620	600×615×1870	360	74	79	230V/50Hz	57
DR600	0 ~ +10	665×580×1660	775×735×1870	580	92	99	230V/50Hz	42
DF600	-10 ~ -22	665×580×1660	775×735×1870	580	96	103	230V/50Hz	42



>> WHITE PAINTED RANGE
UPRIGHT GLASS DOOR CHILLER & FREEZER



↳ G420



↳ G930



↳ D420



↳ D930

Model	Temperature (°C)	Dimension Internal W×D×H (mm)	Dimension External W×D×H (mm)	Net Volume (L)	N.W. (Kg)	G.W. (Kg)	Power (V/Hz)	Loading Qty. 40' Container (units)
G420	+2 ~ +8	560×580×1270	680×720×1990	412	134	146	230V/50Hz	48
G930	+2 ~ +8	1250×580×1270	1370×720×1990	920	224	239	230V/50Hz	24
D420	-18 ~ -20	560×580×1270	680×720×1990	412	138	149	230V/50Hz	48
D930	-18 ~ -20	1250×580×1270	1370×720×1990	920	227	242	230V/50Hz	24



